

## APC308

### 7.62 x 51 mm (.308 Win)

The APC family is finally complete! The introduction of the APC308 in a carbine and a DMR version has fulfilled the long stated goal of B&T to have the APC family of firearms with identical ergonomics and controls in all major calibers (9 x 19 mm, .45 ACP, 5.56 x 45 mm/.223 Remington, .300 Blackout/.300 Whisper and now 7.62 x 51mm (.308 Win).



- Chambered in 7.62 x 51 mm (.308 Win)
- 100% ambidextrous controls
- Hydraulic buffer for light recoil
- Suppressor ready for the ROTEX-IIA
- Five different stock options
- Semi-automatic only

B&T has developed what many say is our finest work. The weapon possesses all the same handling characteristic and controls as all other members of the APC-family. This will reduce transition training time to any of the other APC platforms significantly. But this will not only save time, money, energy and of course needless stress in the classroom or on the range, but also in the armory. As more than 50 % of the parts throughout the APC family are the same, logistic cost are cut significantly as well as service time and costs.

The selector, magazine release, bolt handle, and bolt release are completely ambidextrous. The bolt handle can easily be changed to accommodate either left or right handed shooters. The standard stock folds to the right and can be fired in the closed position. The operator can optimize the weapon to any mission by being able to choose any of the five different stock options available.

The upper receiver is machined from solid aerospace quality alloy. The Picatinny/NAR rails in the 12 and 6 o'clock position are machined into the receiver and are not an add on, so there is nothing to get loose and ruin the weapon's zero. The top rail runs along the entire receiver of the weapon. This provides 420 mm of space to mount any type of optic plus additional NVD, Thermal Sights or Booster on the market. The bottom rails runs 155 mm to accommodate bipods, laser designators or handgrips.

# APC308

## 7.62 x 51 mm (.308 Win)



To accommodate the different needs for a 7.62 x 51 mm (.308 Win) rifle, B&T offers two versions of the APC308: the standard APC308 in a carbine configuration with a 330 mm barrel and the APC308 - DMR with a 480 mm barrel. Both versions have a cold-hammer-forged barrel made in Germany. The 1:12 right hand twist rate is to accommodate the widest range of bullet weights. With match grade ammunition the APC308 will produce 1 MOA accuracy. The barrel is threaded and is delivered with a B&T designed flash hider. This flash hider provides excellent reduction of muzzle flash and will accept the B&T Rotex-IIA suppressor. The Rotex-IIA is widely used in the world by professional users and the perfect choice for the APC308 for all kind of missions. A selector switch in the gas block can be set to „suppressor mode“ in order to provide perfect function when using the suppressor.

The lower receiver group is a precision machined alloy. The adaptable A2-style pistol grip is produced by Magpul and represents the latest in ergonomics and operator comfort. The weapon accepts 7.62 x 51 mm Magpul SR25/M110/AR10 magazines. These are available in 10, 20 and 25-round sizes. The selector and trigger guard are oversized to accommodate gloved hands.

The APC308 is the perfect choice when an Police Carbine or DMR rifle with powerful and long range capable cartridge is needed. As a member of the APC family it offers training, fighting and cost advantages like no other family of weapons on the market.

	APC308	APC308 - DMR
<b>Caliber</b>	7.62 x 51 mm	7.62 x 51 mm
<b>Operation</b>	Short stroke gas piston	Short stroke gas piston
<b>Magazines</b>	10, 20, 25 rounds	10, 20, 25 rounds
<b>Barrel Length</b>	330 mm	480 mm
<b>Twist Rate</b>	1 in 12" right hand	1 in 12" right hand
<b>Weight Empty</b>	4.0 kg with magazine	4.6 kg with magazine
<b>Length Open/Closed</b>	875 / 663 mm	1025 / 813 mm
<b>Width Open/Closed</b>	69 / 100 mm	69 / 100 mm
<b>Height</b>	210 mm	210 mm

All specifications are subject to change without prior notice.  
Data are mean values and therefore not suitable acceptance criteria.



B&T AG  
Tempelstrasse 6  
3608 Thun / Switzerland  
Tel. +41 334 67 00  
info@bt-ag.ch  
www.bt-ag.ch